



**Forming Systems, Inc.**  
P.O. Box 694  
Schoolcraft, MI 49087 USA

Phone: 877-727- FORM (3676)  
269-679-3557 (International)  
Fax: 269-679-3567  
Email: [info@formingsystemsinc.com](mailto:info@formingsystemsinc.com)

# CNC 2 AXES Spring Coiling Machine **HTC 16CS**



## STANDARD 2 SERVO MOTOR:

1	FEED
1	O.D. PITCH CUTTER

## OPTIONAL ACCESSORIES:

ACCESSORIES	SYMBOL
SAFETY COVER	S
TORSION ATTACHMENT	A
SPRING LENGTH GAGE	SLG10
LONG SPRING GUIDE	L

## ENTIRE SERIES:

	WIRE DIA.
HTC 8CS	0.12 – 0.8mm
<b>HTC16CS</b>	<b>0.4 – 1.6mm</b>
HTC40CS	1.8 – 4.0mm

## FEATURES:

- 2 Servo Motors, computer controlled.
- Synchronized programming for high speed spring production.
- Continuous rotation mode insures high-speed production capability.
- Continuous mode and discontinuous mode programming are selectable.
- A Micro Pulse Hand Wheel is used to run every motor either in manual Mode or Auto Mode for very easy setup and programming.
- Easy to read 10 inch color TFT-LCD screen.
- Right hand and left hand coiling.
- Standard security sensor and position sensor included.
- Rotating Cutter is standard accessory for HTC16CS.

## SPECIFICATION:

MODEL	WIRE DIA.	CAM	FEED	MAX. SPEED	DIMENSION (LxWxH)	WEIGHT
HTC 16CS	0.4mm-1.6mm (.016" - .063")	1.5 KW MAX. 300RPM	1.5 KW MAX. 70M/MIN	300PCS/MIN	140x90x175cm (55"x35"x69")	650KGS (1400LBS)

# HTC®